PATENT
Docket: CU-4061 RECEIVED
CENTRAL FAX CENTER

Application Serial No. 10/524,498 Reply to Office Action of July 24, 2007

## **AMENDMENTS TO THE CLAIMS**

OCT 2:3 2007.

**2**002/005

The listing of claims presented below replaces all prior versions, and listings, of claims in the application.

## **LISTING OF CLAIMS:**

- 1. (previously presented) A U-shaped pacifier strap clip with two clamping parts pivotable relative to each other which are formed by the legs of a U-section having co-operating clamping regions, wherein opposing inner-side surfaces of the clamping regions rest against each other in a closed clamping position of the pacifier strap clip and the apex of the U-section is provided as a pivot axis, or pivoting region, respectively, for the clamping parts, the clamping regions of the pacifier strap clip being spaced apart in their relaxed open position, wherein the U-section comprises a fastening bracket for connecting a pacifier strap to the clip, and the U-shaped pacifier strap clip is a two-component injection molded member with a surface of at least one clamping region at least partially being made of a material having a lower hardness than the material of the clamping parts.
- 2. (previously presented) A clip according to claim 1, wherein one clamping region at least partially comprises a surface of the material of lower hardness.
- 3. (previously presented) A clip according to claim 1, wherein at least one clamping region at least partially is formed by a coating of the material of lower hardness.
- (previously presented) A clip according to claim 3, wherein the inner surface of a clamping part in the clamping region is entirely coated with the material of lower hardness.
- 5. (previously presented) A clip according to claim 4, wherein a narrow-side rim of the clamping part in the clamping region is at least partially coated with the material of lower hardness.

Application Serial No. 10/524,498 Reply to Office Action of July 24, 2007

PATENT Docket: CU-4061

- 6. (previously presented) A clip according to claim 1, wherein on each one of the inner surfaces of the clamping region, a tooth profile is provided, the tooth profiles meshing in the clamping position, and at least one tooth profile being made of the material of lower hardness.
- 7. (previously presented) A clamp according to 1, wherein for the transition into the clamping position, a bracket embracing the two clamping parts-and shiftably mounted on the latter is provided.
- 8. (previously presented) A clip according to claim 7, wherein at least one clamping part externally includes at least one wedge-shaped web that widens towards the free end of the clamping part, which web is made of the same material as the U-section.
- 9. (previously presented) A clip according to claim 8, wherein two wedge-shaped webs arranged at the rim side are provided on one clamping part.
- 10. (previously presented) A clip according to claim 8, wherein said at least one wedge-shaped web has a profiled surface.
- 11. (previously presented) A clip according to claim 1, wherein the clamping regions are oval.
- 12. (previously presented) A clip according to claim 1, wherein the clamping parts are made of a hard synthetic material.
- 13. (currently amended) A clip according to claim 1, wherein a thermoplastic elastomer (TPE) is provided as the material of lower hardness.
- 14. (previously presented) A clip according to claim 1, wherein the clip is a two-component injection-molded piece.
- 15. (previously presented) A clip according to claim 12, wherein the hard synthetic material is polycarbonate.